

# J5-WIFI-B / J5-IP-W



- **Commercial Touchscreen Wi-Fi Thermostat**
- **Standard (Gas/Electric) up to 2H/2C**
- **Heat Pump up to 3H/2C**
- **Humidity Sensing & Dehumidification Control**
- **NetX Internal Expansion Port**
- **7 Day Programmable + 80 Calendar Events**
- **Onboard Data Logging**
- **BACnet/IP, Modbus TCP/IP Embedded**

## GENERAL DESCRIPTION:

## Complete Stand-Alone Solution

The J5-WIFI-B (black case) and J5-WIFI-W (white case) are Wi-Fi touchscreen thermostats, designed for new or replacement commercial and residential applications. Use the J5-WIFI for either conventional and heat pump applications (Gas/Elect 2H/2C, HP 3H/2C) with Roof Top, Split, FCU, and other equipment types. The J5-WIFI also has a revolutionary NetX Expansion Port for the NetX CO<sub>2</sub> sensor, NLC Lighting Control, or other future accessories. The powerful processor allows near effortless setup of your daily schedules (4 events per day) and up to 80 Additional Events (40 Special and 40 Calendar Events). The unique scheduling structure also supports the powerful features of adjustable temporary override times and temperature ranges, occupied and unoccupied events, touchscreen lockout, and many more features. In addition to the powerful NetX ecosystem, the J5-WIFI also includes full both Modbus TCP/IP and BACnet/IP over Ethernet, directly on the thermostat.

The J5-WIFI is designed to operate with our CloudConnect™ Online Management software or, for maximum security, behind your firewall using DirectConnect™ to the embedded web server. With all functions stored in the thermostat, the J5-WIFI will continue to operate even during network outages, allowing you to maintain your energy savings. For ultimate control over energy usage, the J5-WIFI offers a digital lockout that can permit limited temperature overrides based on your requirements. The on-board data collection allows for historical review, sub-metering, and run-time reporting.

## STANDARD FEATURES:

## CloudConnect™ & CloudManager™ Available

### Energy Savings

- Efficient Equipment Restart™ randomizes equipment starts to minimize multiple units turning on simultaneously when there are multiple NetX thermostats at the location
- Random Restart on power up staggers restart of HVAC system after a power outage to minimize peak in-rush current
- Adaptive Recovery for Schedules allows system to achieve desired setpoint at the beginning of the schedule

### Monitoring

- NetX Expansion Port for CO<sub>2</sub>, NLC Lighting, and other future accessories
- On-board Data Logging with Sub-Metering Support

### Connectivity

- CloudConnect™ Internet-Based Cloud Service
- PCConnect™ Software Local Network & Port Forwarded Access
- DirectConnect™ Integrated Web Server
- Integrated NetX™ API, Supports 3rd Party Apps
- BACnet/IP and Modbus TCP/IP over Wi-Fi (use either or both)

### Facility Management

- 4 independent schedules per day
- 80 Additional Event Schedules (40 Special and 40 Calendar Events)
- Commercial Lockout with Programmable Temporary Override Time and Temp Adjustment
- Min/Max Heating and Cooling Restrictions
- Email & Text Message Alerting for 4 Locations
- Alerts include High/Low Temps for Indoor, Outdoor, Inefficient Equipment Operation, Change Filter Notifications, and more

### General

- Sleek Black Touchscreen Display with White Icons, Black or White Case
- Modes: Heat, Cool, Automatic Changeover
- Integrated Humidity Sensing and Dehumidification Control
- Fan Selector for Independent Fan Control
- Programmable Recirculation Fan
- Integrated Weather with Current Conditions and 7-Day Forecasts
- Embedded Web Server with responsive design allowing access from any device with a browser



## SPECIFICATIONS:

**Rated Voltage:** 20V to 30VAC, 24VAC nominal

**Rated A.C. / D.C. Current:** 0.05 to 0.75 AC / 0.0 to 0.75 DC Amp continuous, per output, surges to 3 Amps maximum

**Temperature Control Range: Heating:** 38°F to 88°F (4°C to 31°C) in 1° steps **Cooling:** 60°F to 108°F (16°C to 42°C) in 1° steps

**Thermostat Sensing Range:** 32°F to 118°F (0°C to 48°C) **Control Accuracy:** ±1°F @ 68°F (±0.5°C @ 20°C)

**Minimum Deadband:** 2°F (1°C)

**Dimensions:** 5.1"H x 3.25"W x 1.08"D (130mm x 82.5mm x 27.4mm)

**Mounting:** Single Gang Vertical Mount, Standard 3 9/32" Screw Hole Spacing


**Equipment Terminations:** R - 24V Switching Voltage, G - Fan, Y1-Compressor1, Y2 - Compressor2, W1 - Heat1 or Aux/Emer Heat, W2 - Heat2, O/B - Rev. Valve in Cooling, or Heating (Software Defined)

**Power Terminations:** R - 24V Switching Voltage (from HVAC equipment), 24V - Separate Power (24VAC/DC) requires jumper removal, C - Power Return (from HVAC equipment)

**Wireless Radio:** 2.4GHz 802.11b/g/n, Security: Open, WEP, WPA-PSK, WPA2-PSK

**Internal Expansion Port:** SIM port for NetX CO<sub>2</sub> Sensor, NLC Lighting Control, NetX future accessories

## WIRING DIAGRAMS:



## TERMINAL FUNCTIONS

- Y2 Compressor 2
- W1 Heat 1
- Y1 Compressor 1
- G Fan
- O/W2 O - Reversing Valve, Heat 2
- B B - Reversing Valve
- R 24VAC Power
- 24V For Separate RC/RH, Remove Jumper on PCB
- C 24V Return