

J5-IP-B / J5-IP-W



- **Commercial Touchscreen Ethernet Thermostat**
- **Standard (Gas/Electric) up to 2H/2C**
- **Heat Pump up to 3H/2C**
- **Humidity Sensing & Dehumidification Control**
- **NetX Internal Expansion Port**
- **7 Day Programmable + 80 Calendar Events**
- **Onboard Data Logging**
- **BACnet/IP, Modbus TCP/IP Embedded**

GENERAL DESCRIPTION:

The J5-IP-B (black case) and J5-IP-W (white case) are Ethernet touchscreen thermostats, designed for new or replacement commercial and residential applications. Use the J5-IP for either conventional and heat pump applications (Gas/Elect 2H/2C, HP 3H/2C) with Roof Top, Split, FCU, and other equipment types. The J5-IP also has a revolutionary NetX Expansion Port for the NetX CO₂ sensor, NLC Lighting Control, or other future accessories. The powerful processor allows near effortless setup of your daily schedules (4 events per day) and up to 80 Additional Events (40 Special and 40 Calendar Events). The unique scheduling structure also supports the powerful features of adjustable temporary override times and temperature ranges, occupied and unoccupied events, touchscreen lockout, and many more features. In addition to the powerful NetX ecosystem, the J5-IP also includes full both Modbus TCP/IP and BACnet/IP over Ethernet, directly on the thermostat.

The J5-IP is designed to operate with our CloudConnect™ Online Management software or, for maximum security, behind your firewall using DirectConnect™ to the embedded web server. With all functions stored in the thermostat, the J5-IP will continue to operate even during network outages, allowing you to maintain your energy savings. For ultimate control over energy usage, the J5-IP offers a digital lockout that can permit limited temperature overrides based on your requirements. The on-board data collection allows for historical review, sub-metering, and run-time reporting.

Complete Stand-Alone Solution

STANDARD FEATURES:

Energy Savings

- Efficient Equipment Restart™ randomizes equipment starts to minimize multiple units turning on simultaneously when there are multiple NetX thermostats at the location
- Random Restart on power up staggers restart of HVAC system after a power outage to minimize peak in-rush current
- Adaptive Recovery for Schedules allows system to achieve desired setpoint at the beginning of the schedule

Monitoring

- NetX Expansion Port for CO₂, NLC Lighting, and other future accessories
- On-board Data Logging with Sub-Metering Support

Connectivity

- CloudConnect™ Internet-Based Cloud Service
- PConnect™ Software Local Network & Port Forwarded Access
- DirectConnect™ Integrated Web Server
- Integrated NetX™ API, Supports 3rd Party Apps
- BACnet/IP and Modbus TCP/IP over Ethernet (use either or both)

Facility Management

- 4 independent schedules per day
- 80 Additional Event Schedules (40 Special and 40 Calendar Events)
- Commercial Lockout with Programmable Temporary Override Time and Temp Adjustment
- Min/Max Heating and Cooling Restrictions
- Email & Text Message Alerting for 4 Locations
- Alerts include High/Low Temps for Indoor, Outdoor, Inefficient Equipment Operation, Change Filter Notifications, and more

General

- Sleek Black Touchscreen Display with White Icons, Black or White Case
- Modes: Heat, Cool, Automatic Changeover
- Integrated Humidity Sensing and Dehumidification Control
- Fan Selector for Independent Fan Control
- Programmable Recirculation Fan
- Integrated Weather with Current Conditions and 7-Day Forecasts
- Embedded Web Server with responsive design allowing access from any device with a browser

CloudConnect™ & CloudManager™ Available



SPECIFICATIONS:

Rated Voltage: 20V to 30VAC, 24VAC nominal

Rated A.C. / D.C. Current: 0.05 to 0.75 AC / 0.0 to 0.75 DC Amp continuous, per output, surges to 3 Amps maximum

Temperature Control Range: Heating: 38°F to 88°F (4°C to 31°C) in 1° steps **Cooling:** 60°F to 108°F (16°C to 42°C) in 1° steps

Thermostat Sensing Range: 32°F to 118°F (0°C to 48°C) **Control Accuracy:** ±1°F @ 68°F (±0.5°C @ 20°C)

Minimum Deadband: 2°F (1°C)

Dimensions: 5.1"H x 3.25"W x 1.08"D (130mm x 82.5mm x 27.4mm)

Mounting: Single Gang Vertical Mount, Standard 3 9/32" Screw Hole Spacing


Equipment Terminations: R - 24V Switching Voltage, G - Fan, Y1-Compressor1, Y2 - Compressor2, W1 - Heat1 or Aux/Emer Heat, W2 - Heat2, O/B - Rev. Valve in Cooling, or Heating (Software Defined)

Power Terminations: R - 24V Switching Voltage (from HVAC equipment), 24V - Separate Power (24VAC/DC) requires jumper removal, C - Power Return (from HVAC equipment)

Ethernet: 10/100Mbps, 802.3, Auto Negotiation, Auto-DMIX

Internal Expansion Port: SIM port for NetX CO₂ Sensor, NLC Lighting Control, NetX future accessories

WIRING DIAGRAMS:



TERMINAL FUNCTIONS

- Y2 Compressor 2
- W1 Heat 1
- Y1 Compressor 1
- G Fan
- O/W2 O - Reversing Valve, Heat 2
- B B - Reversing Valve
- R 24VAC Power
- 24V For Separate RC/RH, Remove Jumper on PCB
- C 24V Return